

### Description:

Tivoli Stone Admix is a concentrated, waterborne acrylic polymer additive for use with Tivoli Stone Base, Tivoli Stone Antique Stucco, Tivoli Stone Classic and Tivoli Stone Plaster. Tivoli Stone Admix can also be used with most cementitious materials.

### Uses:

Use Tivoli Stone Admix with Tivoli Stone Base and Tivoli Stone Finishes to reduce cracking, increase bond and decrease shrinkage. By using Tivoli-Stone Admix it will improve tensile, tensile bond, flexural and compressive strengths. It will also reduce water absorption. Tivoli Stone Admix will produce a polymer-modified cement that will increase freeze/thaw stability. Tivoli Stone Admix will also reduce the chance of efflorescence.

### Color:

White viscous liquid

### Packaging:

1-gallon plastic bottle- 8.5 lbs.  
(3.62 kg.)  
5-gallon plastic pail- 42.5 lbs.  
(18.1 kg.)

### Mixing:

Mix Tivoli Stone Admix in a well ventilated area. Safety goggles, gloves and respirator are recommended when using this product alone or in conjunction

with any material. Remove contaminated clothing immediately. Shake 1 gallon bottle vigorously before use. Mix 5 gallon pail with drill mixer for 1 minute before use. Do not dilute with water.

### Storage:

Store in a cool dry location. Keep from freezing. Keep out of direct sunlight for prolonged periods. Do not store at temperatures above 90°F or below 40°F.

### Shelf Life:

1 year

### Limitations:

Tivoli Stone Admix should be used with cementitious materials being applied between 45°F and 100°F. Tivoli Stone Admix will create incredible bonding characteristics but **can not** be used over moist or frozen substrates.

### Surface Preparation:

When using Tivoli Stone Admix with Tivoli Stone Base and finishes, surfaces must be clean and free of bond-inhibiting materials such as dirt, dust, rust, grease, oil, efflorescence, mildew, fungus, form-release agents, or any other contaminants. Failure to correctly prepare the surface may result in product failure.

### Curing/Drying:

Drying time for modified Tivoli Stone materials will decrease slightly but will vary depending

on ambient temperature, humidity and thickness of application. Use of Tivoli Stone Admix may increase open time of original cementitious products by 5-10%. Material will dry completely with 24 hours unless being used in high humidity environments. To slow down set time ice may be added to Tivoli Stone Admix.

### Clean Up:

Clean tools and equipment with water immediately after use.

### First Aid:

**SKIN CONTACT:** Wash thoroughly with soap and water.  
**EYE CONTACT:** Flush immediately with water for 10-15 minutes and contact a physician.

### Spills:

Wipe up with absorbent towel or rag. Wash area with water immediately.

### Disposal:

Dispose of in accordance with local, state or federal regulations.

### Warning:

**KEEP OUT OF REACH OF CHILDREN. NOT FOR INTERNAL CONSUMPTION. FOR INDUSTRIAL USE ONLY.**